


Smart Protections Texwrap

Textile wrapping sleeve

Part Number	Internal Round Diameter Inches	Flat Open Width	Weight per Roll Each Roll 164'
			
TEXW-35	1.38	5.83	8.80
TEXW-50	1.97	7.76	11.88
TEXW-75	2.95	11.65	16.28
TEXW-100	3.94	13.82	18.81
TEXW-125	4.92	16.85	22.22
TEXW-150	5.91	20.67	26.62
TEXW-175	6.89	23.31	29.70
TEXW-200	7.87	26.22	32.78



HOSE PROTECTION
AND
PEOPLE PROTECTION
MSHA IC-207/02

Standard Version



Special Version with eyelets



Texwrap is a foldable sleeve made of polyamide fibers coated on one side with UV-resistant PU. The exclusive locking system, made of highly resistant VCO (Velcro) allows to obtain a tubular protection of endless length and easy to assemble. **Texwrap** can be supplied in customized versions: cut to size and stitched, with the addition of eyelets and locking catch to improve resistance.

Standard Color: Black - Other colors available upon request

Temperature Range: -40°C to +180°C (-40°F to + 356°F)

MSHA Approval for mining applications IC 207/02

Volume resistivity (applied voltage 500V) Ω. M 5,9.10¹² according to CEI 15-23

Surface resistivity (applied voltage 500V) Ω. 1,4.10¹⁶ according to CEI 15-23